

Declaration of Performance

- Nr.: DoP KKplus s1 01032018001
1. Unique identification code of the product-type: FEF Kaiflex KKplus s1
 2. Intended use/es: Thermal insulation for technical building equipment and industrial installations (ThIBell).
 3. Manufacturer: Kaimann GmbH
Hansastraße 2-5
D-33161 Hövelhof
 4. Authorised representative: Not relevant
 5. System/s of AVCP: 1
 6. a. Harmonised standard: Declaration of performance according to product standard EN 14304:2009+A1:2013.
Notified body/ies: 0751 "Forschungsinstitut für Wärmeschutz e.V. München"
 - b. European Assessment Document: Not relevant
 7. Declared performance/s:

Essential Features		Performance				
Reaction to fire euroclass-characteristics	Reaction to fire	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	B-s1, d0 B _L -s1, d0			
Acoustic absorption index	Structure-borne noise transmission Acoustic absorption		NPD			
Thermal resistance	Thermal conductivity Dimensions and limits	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	°C W/(m·K)	-10°C 0,037	0°C 0,038*	10°C 0,039
Water permeability	Water absorption		WS01 (W _p ≤ 0,1 kg/m ²)			
Water vapour permeability	Water vapour diffusion resistance	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	MU 10.000 (μ ≥ 10.000)			
Release of corrosive substances	Minor amounts of water soluble chlorides and pH-value		300/7			
Release of dangerous substances to indoor environment	Release of dangerous substances		NPD ^a			
Continuous glowing combustion	Continuous glowing combustion		NPD			
Durability of reaction to fire against ageing/degradation	Durability characteristics ^b					
Durability of thermal resistance against ageing/degradation	Durability characteristics ^c					
	Maximum service temperature	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	ST(+) 85°C ST(+) 110°C			
	Minimum service temperature	Sheet: d _N = 3 - 32 mm Tube: d _N = 9 - 32 mm	ST(-) -50°C			
Durability of reaction to fire against high temperature	Durability characteristics ^b					
Durability of thermal resistance against high temperature	Durability characteristics ^c					

a No test method yet adopted.

b The fire performance of flexible elastomeric foam does not change with time.

c The thermal conductivity of flexible elastomeric foam does not change with time.

NPD= No Performance Determined

*λ_s ≤ 0,038 + 8,0 · 10⁻⁶ θ + 1,2 · 10⁻⁷ θ²

8. Appropriate Technical Documentation and/or Specific Technical Documentation: The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wolfgang Lewandowski, Manager Produktqualität und -compliance

Hövelhof/01.03.2018

