

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Substances / Trade name / designation: Kaiflex K 414 glue

Index No.: Not applicable.

EC No.: Not applicable.

CAS No.: Not applicable.

REACH Registration No.: Not applicable.

**Other means of identification:** Kaiflex K 414 glue.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture:

Adhesives.

Uses advised against:

Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

##### **Manufacturer/Supplier:**

Kaimann GmbH

##### **Address**

Hansastraße 2-5

D-33161 Hövelhof

##### **Department issuing data specification sheet**

Kaimann GmbH - Technik

##### **Phone / Fax / E-Mail**

+49 (0) 5257-9850-0 / +49 (0) 5257-9850-590/ E-Mail: msds@kaimann.de

#### 1.4 Emergency telephone number

Advice Center for Poison Symptoms and Embryo Toxicology (Emergency Phone Line Berlin / Giftnotruf Berlin)

Tel.: +49 (0) 30 -1 92 40 · www.giftnotruf.de

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms:



Signal word: Danger

##### Hazard components for labeling:

Ethyl acetate

Naphtha, hydrotreated light

##### Hazard statements:

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370 + P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

##### Additional information

Contains Rosin. May produce an allergic reaction.

#### 2.3 Other hazards

##### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### SECTION 3: Composition / information on ingredients

#### 3.2 Mixtures

**Description:** Adhesive

#### **Dangerous components**

ETHYL ACETATE	registration number: 01-2119475103-46 EINECS: 205-500-4 ; CAS: 141-78-6 ; Percentage: 25-< 35 % Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336
NAPHTHA, HYDROTREATED LIGHT	registration number: 01-2119486291-36 EC number: 926-605-8; Percentage: 20-< 25 % Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic. 2; H411; Skin. Irrit.2, H315; STOT SE 3, H336
NAPHTHENE	registration number: 01-2119475515-33 EC number: 927-510-4; Percentage: 10-< 15 % Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic. 2, H411; Skin. Irrit. 2, H315; STOT SE 3, H336
NAPHTHA, HYDROTREATED LIGHT	registration number: 01-2119484651-34 EC number: 931-254-9; Percentage: 5-< 10 % Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic. 2, H411; Skin. Irrit. 2, H315; STOT SE 3, H336
SOLVENT NAPHTHA	registration number: 01-2119486291-36 EC number: 926-605-8; Percentage: 2.5-< 5 % Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic. 2, H411; STOT SE 3, H336
ACETONE	registration number: 01-2119471330-49 EINECS: 200-662-2; CAS: 67-64-1; Percentage: 2.5-< 5 % Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336
ROSIN	registration number: 01-2119480418-32 EINECS: 232-475-7; CAS: 8050-09-7; Percentage: 0.1-< 0.5 % Skin. Sens.1, H317

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

n-HEXANE

registration number: 01-2119480412-44

EINECS: 203-777-6; CAS: 110-54-3; Percentage: 0.25-< 0.5 %

Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE2, H373;  
Asp. Tox. 1, H304; Aquatic Chronic. 2, H411; Skin Irrit.2,  
H315; STOT SE 3, H336

### Additional information:

If any R-phrases (risk-phrases) are listed, please refer for the exact wording to section 16.  
Contains < 0.1 % benzene (Note P).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information:

Take affected persons into the open air.

#### After inhalation:

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult physician in case of symptoms.

#### After skin contact:

Instantly wash with water and soap and rinse thoroughly.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult physician.

#### After swallowing:

In case of persistent symptoms consult physician.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water. Water with a full water jet.

### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire: Carbon monoxide (CO).

### 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### 6.2 Environmental precautions

Do not allow product to reach sewage system or water bodies.  
Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.  
Prevent from spreading (e.g. by damming-in or oil barriers).

### 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.  
Ensure good ventilation/extraction system at the workplace.  
Open and handle container with care.  
Ensure good interior ventilation, especially at floor level (Fumes are heavier than air).

#### **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Use only in explosion-proof area.  
Highly volatile, flammable constituents are released during processing.  
Fumes can combine with air to form an explosive mixture.  
Flammable mixtures may be formed in empty containers.

### 7.2 Conditions for safe storage, including any incompatibilities

#### **Storage:**

**Requirements to be met by storerooms and containers:** Store in cool location.

**Information about storage in one common storage facility:** Not required.

#### **Further information about storage conditions**

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed containers.

**Storage class:** 3

### 7.3 Specific end use(s)

No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### **Additional information about design of technical systems:**

No further data; see item 7.

### 8.1 Control parameters

#### **Components with critical values that require monitoring in the workplace**

ETHYL ACETATE WEL Short-term value: 400 ppm  
(CAS: 141-78-6) WEL Long-term value: 200 ppm

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

ACETONE (CAS: 67-64-1)	WEL Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm WEL Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
ROSIN (CAS: 8050-09-7)	WEL Short-term value: 0.15 mg/m <sup>3</sup> WEL Long-term value: 0.05 mg/m <sup>3</sup>
n-HEXANE (CAS: 110-54-3)	WEL Long-term value: 72 mg/m <sup>3</sup> , 20 ppm

### Derived no-effect level (DNELs)

#### Worker

ETHYL ACETATE (CAS: 141-78-6)	Dermal: DNEL w 63 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL w 1468 mg/m <sup>3</sup> (acute, local effects) DNEL w 1468 mg/m <sup>3</sup> (acute, systemic effects) DNEL w 734 mg/m <sup>3</sup> (long-term, local effects) DNEL w 734 mg/m <sup>3</sup> (long-term, systemic effects)
NAPHTHA, HYDROTREATED LIGHT	Dermal: DNEL w 25.9 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL w 3.25 mg/m <sup>3</sup> (long-term, systemic effects)
NAPHTHENE	Dermal: DNEL w 300 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL w 2085 mg/m <sup>3</sup> (acute, systemic effects)
NAPHTHA, HYDROTREATED LIGHT	Dermal: DNEL w 13964 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL w 5306 mg/m <sup>3</sup> (long-term, systemic effects)
SOLVENT NAPHTHA	Dermal: DNEL w 13964 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL w 5306 mg/m <sup>3</sup> (long-term, systemic effects)

#### DNEL

##### Consumer

ETHYL ACETATE (CAS: 141-78-6)	Oral: DNEL c 4,5 mg/kg bw/day (long-term, systemic effects) Dermal: DNEL c 37 mg/kg bw/day (long-term, systemic effects) Inhalative: DNEL c 734 mg/m <sup>3</sup> (acute, local effects) DNEL c 734 mg/m <sup>3</sup> (acute, systemic effects) DNEL c 367 mg/m <sup>3</sup> (long-term, local effects) DNEL c 367 mg/m <sup>3</sup> (long-term, systemic effects)
----------------------------------	--

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### NAPHTHENE

Oral:  
DNEL c 149 mg/kg bw/day (long-term, systemic effects)  
Dermal:  
DNEL c 149 mg/kg bw/day (long-term, systemic effects)  
Inhalative:  
DNEL c 477 mg/m<sup>3</sup> (long-term, systemic effects)

### NAPHTHA, HYDROTREATED LIGHT

Oral:  
DNEL c 1301 mg/kg bw/day (long-term, systemic effects)  
Dermal:  
DNEL c 1377 mg/kg bw/day (long-term, systemic effects)  
Inhalative:  
DNEL c 1137 mg/m<sup>3</sup> (long-term, systemic effects)

### SOLVENT NAPHTHA

Oral:  
DNEL c 1301 mg/kg bw/day (long-term, systemic effects)  
Dermal:  
DNEL c 1377 mg/kg bw/day (long-term, systemic effects)  
Inhalative:  
DNEL c 1131 mg/m<sup>3</sup> (long-term, systemic effects)

### Predicted no-effect concentration (PNECs)

#### ETHYL ACETATE (CAS: 141-78-6)

Oral:  
PNEC oral 0,2 mg/kg food (n.a.)  
PNEC sediment 1,25 mg/kg (sediment, freshwater)  
PNEC sediment 0,125 mg/kg (sediment, marine water)  
PNEC soil 0,24 mg/kg (soil)  
PNEC water 0,26 mg/l (freshwater)  
PNEC water 1,65 mg/l (intermittent release)  
PNEC water 0,026 mg/l (marine water)  
PNEC water 650 mg/l (STP, sewage treatment plant)

**Additional information:** The lists that were valid during the compilation were used as basis.

## 8.2 Exposure controls

### Additional information about design of technical systems:

No further data; see item 7.

### Personal protective equipment:

#### General protective and hygienic measures:

Standard precautionary measures for handling chemicals are to be observed.  
Keep away from food, beverages and animal feed.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

#### Breathing equipment:

Use breathing protection in case of insufficient ventilation (EN 14387).  
Short term filter device:  
Filter AX (boiling point < 61 °C); Filter A (boiling point > 60 °C).  
Only when applied by spray methods, if no adequate extraction system is in place (EN 149).  
Filter A/P2

**Protection of hands:** Impervious gloves (EN 374).

#### Material of gloves

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

Recommended thickness of the material:  $\geq 0.7$  mm

LLDPE gloves.

**Penetration time of glove material:** Value for the permeation: Level  $\leq 1$

**Gloves made of the following material are suitable for the permanent contact with this material in work areas which do not have an above-average risk of injury (e.g. laboratories):**

LLDPE gloves

**For the permanent contact gloves made of the following materials are suitable:** LLDPE gloves

**For permanent contact of max. 15 minutes, gloves made of the following materials are suitable:** Butyl rubber, BR

**To protect against splashing, gloves made of the following materials are suitable:** Chloroprene rubber, CR

**Not suitable are gloves made of the following materials:**

Leather gloves

Strong gloves.

### Eye protection

Safety glasses recommended during refilling and spraying.

Safety glasses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	fluid
Colour:	according to product specification
Smell:	characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition:	
Melting point/freezing point:	Not determined.
Initial boiling point and boiling range:	60 °C
Flash point:	-21 °C
Inflammability (solid, gaseous):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Spontaneous combustion:	Product does not undergo spontaneous combustion.
Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible

Critical values for explosion:

Lower:	1.1 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	110 hPa
Density at 20 °C	0.85 g/cm <sup>3</sup>
Relative density:	Not determined.
Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with Water:	
distribution ratio (n-octanol/water):	Not determined.
Viscosity:	
dynamic at 20 °C:	600 mPas
kinematic:	Not determined.
Solvent content:	
Organic solvents:	81.5 %
Solid content:	18.5 %

Page : 8 / 14

The information supplied on this safety data sheet complies with our current level of knowledge and is not to be regarded as guaranteed attributes of the product.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### 9.2 Other information

No further relevant information available.

#### VOC - Volatile Organic Compounds

European Union	81.48 %
Switzerland	81.48 %
U.S.A (less water and less exempts)	690.2 g/l / 5.76 lb/gl

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No further relevant information available.

### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

### 10.3 Possibility of hazardous reactions

Forms explosive gas mixture with air.  
Develops readily flammable gases / fumes.  
Reacts with strong acids and alkali.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Forms explosive gas mixture with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

### 10.4 Conditions to avoid

No further relevant information available.

### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

Hydrocarbons  
Inflammable gases/vapours  
Carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

ETHYL ACETATE (CAS: 141-78-6)	Oral:
	LD50 oral 5600 mg/kg (rabbit)
	Dermal:
	LD50 dermal 18000 mg/kg (rabbit)

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

NAPHTHA, HYDROTREATED LIGHT	Oral: LD50 oral 5500 mg/kg (rat) Dermal: LD50 dermal > 8000 mg/kg (rabbit) Inhalative: LC50 / 4 h 43.7 mg/l (rat)
NAPHTHA, HYDROTREATED LIGHT	Dermal: LD50 dermal > 8000 mg/kg (rabbit) Inhalative: LC50 / 4 h 43.7 mg/l (rat)
SOLVENT NAPHTHA	Oral: LD50 oral 5500 mg/kg (rat) Inhalative: LC50 / 4 h 50 mg/l (rat)

### Primary irritant effect:

#### to the skin:

Causes skin irritation.

#### to the eye:

Causes serious eye irritation.

### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

### STOT-single exposure:

May cause drowsiness or dizziness.

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

ETHYL ACETATE (CAS: 141-78-6)	LC50 / 96 h: 431 mg/l (zebrafish) LC50 / 96 h: 230 mg/l (rainbow trout) LC50 / 96 h: 230 mg/l (fathead minnow) LC50 / 48 h: 350 mg/l (orfe (ide)) LC50: 200 mg/l (rat) EC50 / 48 h: 3300 mg/l (green algae) EC50 / 48 h: 165 mg/l (water flea) EC50 / 24 h: 724 mg/l (water flea) EC50: 17.9 mg/l (green algae)
NAPHTHA, HYDROTREATED LIGHT	LC50 / 96 h: 14.1 mg/l (rainbow trout) LC50 / 48 h: 10 mg/l (orfe (ide)) EC50 / 48 h: 3 mg/l (water flea) EC50 / 72 h: 75.6 mg/l (green algae)

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

NAPHTHA, HYDROTREATED LIGHT	LC50 / 96 h: 14.1 mg/l (rainbow trout)
	LC50 / 48 h: 10 mg/l (orfe (ide))
	EC50 / 48 h: 6.96 mg/l (water flea)
	EC50 / 72 h: 75.6 mg/l (green algae)
SOLVENT NAPHTHA	LC50 / 96 h: 12 mg/l (rainbow trout)
	EC50 / 48 h: 3 mg/l (water flea)
	EC50 / 72 h: 55 mg/l (green microalgae)

### 12.2 Persistence and degradability

No further relevant information available.

### 12.3 Bioaccumulative potential

No further relevant information available.

### 12.4 Mobility in soil

No further relevant information available.

#### Ecotoxicological effects:

Remark: Toxic for fish.

### Behaviour in sewage plants

ethyl acetat (CAS: 141-78-6)

EC 10 / 16 h

2900 mg/l (pseudomonas putida)

### Additional ecological information

#### General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow the product to reach ground water, open water or the sewer system, undiluted or in large quantities.

Also poisonous for fish and plankton in water bodies.

The product contains materials that are harmful to the environment.

Toxic for aquatic organisms.

### 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

### 12.6 Other adverse effects

No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

#### European waste catalogue

08 04 09: waste adhesives and sealants containing organic solvents or other hazardous substances.

#### Uncleaned containers/packaging material

##### Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

Recommended cleaning agent: Solvent naphtha.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

### SECTION 14: Transport information

#### 14.1 UN-Number

ADR, IMDG, IATA

UN 1133

#### 14.2 UN proper shipping name

ADR  
IMDG  
IATA

1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS  
ADHESIVES (Naphtha, Naphthene), MARINE POLLUTANT  
ADHESIVES

#### 14.3 Transport hazard class(es)

ADR:



Class: 3 (F1) Flammable liquids.

Label: 3

IMDG:



Class: 3 Flammable liquids

Label: 3

IATA:



Class: 3 Flammable liquids

Label: 3

#### 14.4 Packing group

ADR, IMDG, IATA

II

#### 14.5 Environmental hazards

Product contains environmentally hazardous substances: naphthalene

**Marine pollutant:**

No

Yes

Symbol (fish and tree)

Symbol (fish and tree)

**Special marking (ADR):**

#### 14.6 Special precautions for user

Warning: Flammable liquids.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

**Kemler Number:** 33  
**EMS Number:** F-E,S-D  
**Stowage Category:** A

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

#### Transport/Additional information:

##### ADR

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E

##### IMDG

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

##### UN "Model Regulation"

UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Direktive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

#### Seveso category

E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

These data are based on our present knowledge. They shall, however, not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. All standard industrial precautions apply, concerning protection of health, and safe handling. The recommendations have to be examined in the context of the application for which the product is intended, and observed as necessary.

### 16.1 Abbreviations and acronyms

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association

# Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Print date: 29.05.2017  
Revision date: 29.05.2017  
Valid from: 29.05.2017  
Version: 3

Replaces version: 2

## KAIFLEX® Spezialkleber K 414 / KAIFLEX® glue K 414

GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

### 16.2 Relevant R-, H- and EUH-phrases (number and full text)

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.